

ISUZU CREW CAB RIGHT HAND DRIVE

SPECIFICATIONS
SOUTH EAST AFRICA



ISUZU
Delivers

MODEL	250	250	250	300
TRIM	Base+ HR (A/C, A/Bag)	Base (w/o A/Bag, with A/C)	Base+ (A/C, A/Bag)	LX/LS
DRIVE CONFIGURATION	4x2	4x4	4x4	4x4
SMOD	M120T95	M120T97	M120TA1	M120TA3
Engine				
Engine Code	4JK1-TC SO	4JK1-TC SO	4JK1-TC SO	4JJ1-TC SO
Displacement (cc)	2499	2499	2499	2999
No. of Cylinders	4	4	4	4
No. of Valves	16	16	16	16
Power (kW) @ r/min	80 @ 3600	80 @ 3600	80 @ 3600	100 @ 3600
Torque (Nm) @ r/min	280 @ 1800-2200	280 @ 1800-2200	280 @ 1800-2200	280 @ 1200-3400
Fuel System	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection
Turbocharger	•	•	•	•
Intercooler	•	•	•	•
Fuel Type / Recommended Grade	Diesel / Premium Grade	Diesel / Premium Grade	Diesel / Premium Grade	Diesel / Premium Grade
Transmission				
Transmission Type	5-Speed Manual	5-Speed Manual	5-Speed Manual	5-Speed Manual
4WD Rotary Switch Control - 2-Speed Transfer Case	-	•	•	•
Low Range Ratio	-	2,482	2,482	2,482
Front Differential				
Auto Locking Shift on the Fly	-	•	•	•
Axle Ratio: Final Drive	-	3,909	4,1	4,3
Rear Differential				
Differential Lock	•	•	•	•
Axle Ratio: Final Drive	3,909	3,909	4,1	4,3
Chassis Design				
Wheel Suspension Front	Coil Spring	Coil Spring	Coil Spring	Coil Spring
Wheel Suspension Rear	Leaf Spring Overslung	Leaf Spring Overslung	Leaf Spring Overslung	Leaf Spring Overslung
Shock Absorbers	Twin-tube Gas Pressurised	Twin-tube Gas Pressurised	Twin-tube Gas Pressurised	Twin-tube Gas Pressurised
Hi-ride Suspension	•	•	•	•
Skid Plate Guard	•	•	•	•
Engine Sump Guard	•	•	•	•
Transfer Case Guard	-	•	•	•
Fuel Tank Guard	•	•	•	•
Wheel / Tyres				
Tyre Size	205 R16C (AT)	205 R16C (AT)	245/70 R16 (AT)	245/70 R16 (AT)
Wheel Type / Size	Steel 6.5J x 16	Steel 6.5J x 16	Alloy 7J x 16	Alloy 7J x 16
Full Size Spare Wheel / Size	Steel 6.5J x 16	Steel 6.5J x 16	Alloy 7J x 16	Alloy 7J x 16
Dimensions				
Length (mm)	5294	5191	5294	5294
Width (mm)	1860	1860	1860	1860
Height (mm)	1790	1790	1790	1790
Wheelbase (mm)	3095	3095	3095	3095
Track Front / Rear (mm)	1570 / 1570	1570 / 1570	1570 / 1570	1570 / 1570
Ground Clearance (mm)	224	224	224	224
Loadbox Length (mm)	1483	1483	1483	1483
Loadbox Width (mm)	1534	1534	1534	1534
Loadbox Depth (mm)	465	465	465	465
Approach Angle (°)	30,0	30,0	30,0	30,0
Departure Angle (°)	22,7	22,7	22,7	22,7
Breakover Angle (°)	22,4	22,4	22,4	22,4
Wading Depth (mm)	600	600	600	600
Mass / Capacity				
Gross Vehicle Mass (GVM) (kg)	2850	2950	2950	2950
Gross Combined Mass (GCM) (kg)	4450	4950	4950	4950
Towing Capacity (kg): Unbraked Trailer (#1)	750	750	750	750
Towing Capacity / Towbar Rating (kg): Trailer with Overrun Brake (#1)	2100	2100	2100	2100
Fuel Tank Capacity (l)	80	80	80	80
Safety Features				
Anti-lock Brakes (ABS)	-	-	•	•
Electronic Brake-force Distribution (EBD)	-	-	•	•
Brake Assist System (BAS)	-	-	•	•
Side Impact Protection Bars	•	•	•	•
Height Adjustable 3-Point Seatbelts	•	•	•	•

MODEL	250	250	250	300
TRIM	Base+ HR (A/C, A/Bag)	Base (w/o A/Bag, with A/C)	Base+ (A/C, A/Bag)	LX/LS
DRIVE CONFIGURATION	4x2	4x4	4x4	4x4
SMOD	M120T95	M120T97	M120TA1	M120TA3
Seatbelt Pre-tensioners	•	-	•	•
Driver and Front Passenger Airbags	•	-	•	•
Collapsible Steering Column	•	•	•	•
ISOFIX Child Seat Attachment	-	-	-	•
Security Features				
Datadot Vehicle Identification	•	•	•	•
Interior / Exterior Lighting				
Front Reading Lights	-	-	-	•
Interior Courtesy Lights	•	•	•	-
Front Fog Lights	•	-	•	•
Halogen Headlights	Multi-reflector	Multi-reflector	Multi-reflector	Projector
Headlamps "On" Warning Buzzer	•	•	•	•
Rear LED Combination Tail-lights	-	-	-	•
Exterior Features				
Radiator Colour	Material Grey	Material Grey	Material Grey	Chrome
Front Bumper Colour	Body Colour	Material Grey (Wide)	Body Colour	Body Colour
Rear Bumper Colour	Black & Painted Silver	-	Black & Painted Silver	Black & Chrome
Exterior Door Handle Colour	Material Black	Material Black	Material Black	Chrome
Exterior Mirror Colour	Black	Black	Black	Chrome with Side Indicator
Side Steps (Running Board)	-	-	-	•
Interior Features				
Power Assisted Steering	•	•	•	•
Height Adjustable Steering Column	•	-	•	•
Leather Steering Wheel with Multifunction Controls	-	-	-	•
Gearknob Trim	Urethane	STD (C/O)	Urethane	Urethane & Chrome
Front Seats Configuration	2 x Base Bucket	2 x Base Bucket	2 x Base Bucket	2 x Deluxe Bucket
Seat Trim	Cloth	Cloth	Cloth	Luxury Cloth
Height Adjustable Driver Seat	-	-	-	•
Storage Pockets Behind Front Seats	-	-	-	•
Air Conditioner	Manual	Manual	Manual	Manual
Cabin Air Filter (Pollen)	•	•	•	•
Rear Heater Duct	•	•	•	•
Anti-dazzle Rear-view Mirror	Std	Std	Std	Std
Exterior Mirrors	Manual	Manual	Manual	Electrically Adjustable
Electrically Operated Windows	•	-	•	•
12-V Auxiliary Power Supply	2	2	2	2
Illuminated & Lockable Glove Box	-	-	-	•
Door Trim with Storage Pockets and Integrated Cupholders	•	•	•	•
Centre Console Storage Box with Lid	•	•	•	-
Centre Console Storage Box with Lid and Integrated Rear Cupholders	-	-	-	•
Fixed Rear Window, Tinted with no Defogger	-	•	-	-
Fixed Rear Window, Tinted with Defogger	•	-	•	•
Infotainment				
No. of Speakers	4	2	4	6
Radio Ready for Models without Audio System	•	•	•	•
Options				
16" Alloy Wheels & 205R16C Tyres (All Terrain)	•	•	-	-
16" Alloy Wheels & 245/70 R16C Tyres (All Terrain)	•	•	-	-
17" Alloy Wheels & 255/65 R17 Tyres (All Terrain)	-	-	•	•
Sliding Rear Window (Cab Slider)	•	•	•	•
Chrome Sports Bar	-	-	-	•
Silver Painted Sports Bar	•	•	•	-
Seat Trim Leather with Manual Adjustable Driver Seat	-	-	-	•
Warranty				
Warranty	3 Years/100 000 km	3 Years/100 000 km	3 Years/100 000 km	3 Years/100 000 km
Anti-corrosion Warranty	3 Years/Unlimited km	3 Years/Unlimited km	3 Years/Unlimited km	3 Years/Unlimited km

Disclaimer: Abridged specifications above correct as at time of printing and may subsequently change. Refer to brochure for detailed specifications. Please contact your nearest dealer to confirm any specification changes. Date of print March 2013.

Notes: (#1) Towing capacity subject to country specific regulations. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0L 4x4 Diesel is towing 2,100kg its maximum Vehicle mass is 2,850kg in order to be within GCM of 4,950kg)

Available	•
Not Available	-