

# ISUZU REGULAR CAB LEFT HAND DRIVE (DIESEL)

SPECIFICATIONS

SUB-SAHARAN AFRICA



**ISUZU**  
Delivers



MODEL	250	250
TRIM	Base	Base (A/C)
DRIVE CONFIGURATION	4x2	4x4
SMOD	M120T87	M120T91
<b>Engine</b>		
Engine Code	4JA1-L	4JK1-TC SO
Displacement (cc)	2499	2499
No. of Cylinders	4	4
Compression Ratio	18.5:1	18.3:1
Bore x Stroke (mm)	93x92	95.4x87.4
No. of Valves	8	16
Power (kW) @ r/min	58 @ 3800	80 @ 3600
Torque (Nm) @ r/min	176 @ 1800	280 @ 1800-2200
Fuel System	Direct Injection	Common Rail Direct Injection
Turbocharger	•	•
Intercooler	-	•
Fuel Type / Recommended Grade	Diesel / Premium Grade	Diesel / Premium Grade
<b>Transmission</b>		
Transmission Type	5-Speed Manual	5-Speed Manual
4WD Rotary Switch Control - 2-Speed Transfer Case	-	•
Low Range Ratio	-	2,482
<b>Front Differential</b>		
Auto Locking Shift on the Fly	-	•
Axle Ratio: Final Drive	-	3,909
<b>Rear Differential</b>		
Differential Lock	-	•
Axle Ratio: Final Drive	4,3	3,909
<b>Chassis Design</b>		
Wheel Suspension Front	Coil Spring	4x4 Coil Spring
Wheel Suspension Rear	Leaf Spring Underslung	Leaf Spring Overslung
Shock Absorbers	Twin-tube Gas Pressurised	Twin-tube Gas Pressurised
Hi-ride Suspension	-	•
Skid Plate Guard	•	•
Engine Sump Guard	-	•
Transfer Case Guard	-	•
Fuel Tank Guard	•	•
<b>Wheel / Tyres</b>		
Tyre Size	195 R15C (HWY)	205 R16C (AT)
Wheel Type / Size	Steel 6J x 15	Steel 6.5J x 16
Full Size Spare Wheel / Size	Steel 6J x 15	Steel 6.5J x 16
Turning Circle: Tyres (m)	12,3	12,7
Turning Circle: Body (m)	13,5	13,5
<b>Dimensions</b>		
Length (mm)	5218	5218
Width (mm)	1766	1860
Width incl Mirrors (mm)	2132	2132
Height (mm)	1690	1790
Wheelbase (mm)	3095	3095
Track Front / Rear (mm)	1510 / 1510	1570 / 1570
Ground Clearance (mm)	202	224
Loadbox Length (mm)	2318	2318
Loadbox Width (mm)	1534	1534
Loadbox Depth (mm)	440	440
Approach Angle (°)	21,0	30,0
Departure Angle (°)	17,2	22,4
Breakover Angle (°)	17,6	22,4
Wading Depth (mm)	400	600
<b>Mass / Capacity</b>		
Gross Vehicle Mass (GVM) (kg)	2850	2950
Gross Combined Mass (GCM) (kg)	4450	4950
Towing Capacity (kg): Unbraked Trailer (#1)	750	750
Towing Capacity / Towbar Rating (kg): Trailer with Overrun Brake (#1)	2100	2100

MODEL	250	250
TRIM	Base	Base (A/C)
DRIVE CONFIGURATION	4x2	4x4
SMOD	M120T87	M120T91
Fuel Tank Capacity (l)	80	80
<b>Loadbox Features</b>		
Tie-down Brackets in Loadbox for Load Restraint	4	4
Rope Hooks on Loadbox Side	10	10
<b>Safety Features</b>		
Side Impact Protection Bars	•	•
Height Adjustable 3-Point Seatbelts	•	•
Front Seat Centre Lap Belt (2-Point)	•	•
Collapsible Steering Column	•	•
<b>Security Features</b>		
Datadot Vehicle Identification	•	•
<b>Interior / Exterior Lighting</b>		
Interior Courtesy Lights	•	•
Halogen Headlights	Multi-reflector	Multi-reflector
Headlamps "On" Warning Buzzer	•	•
<b>Exterior Features</b>		
Radiator Colour	Material Grey	Material Grey
Front Bumper Colour	Material Grey (Narrow)	Material Grey (Wide)
Exterior Door Handle Colour	Material Black	Material Black
Exterior Mirror Colour	Black	Black
Mudflaps	•	•
<b>Interior Features</b>		
Power Assisted Steering	•	•
Gearknob Trim	Urethane	Urethane
Front Seats Configuration	Split Bench	Split Bench
Seat Trim	PVC	PVC
Floor Trim	Vinyl	Vinyl
Driver Footrest	•	•
Air Conditioner	-	Manual
Cabin Air Filter (Pollen)	-	•
Anti-dazzle Rear-view Mirror	Std	Std
Digital Clock	•	•
Exterior Mirrors	Manual	Manual
12-V Auxiliary Power Supply	2	2
Smokers Pack	•	•
Door Trim with Storage Pockets and Integrated Cupholders	•	•
Fuel Flap Remote	•	•
Side Windows Tinted	•	•
Fixed Rear Window, Tinted with no Defogger	•	•
<b>Infotainment</b>		
No. of Speakers	2	2
Radio Ready for Models without Audio System	•	•
<b>Options</b>		
16" Alloy Wheels & 205R16C Tyres (All Terrain)	-	•
16" Alloy Wheels & 245/70 R16C Tyres (All Terrain)	-	•
Rear Differential Lock	•	-
Sliding Rear Window (Cab Slider)	•	•
Silver Painted Sports Bar	•	•
<b>Warranty</b>		
Warranty	3 Years/100 000 km	3 Years/100 000 km
Anti-corrosion Warranty	3 Years/Unlimited km	3 Years/Unlimited km

**Disclaimer:** Abridged specifications above correct as at time of printing and may subsequently change. Refer to brochure for detailed specifications. Please contact your nearest dealer to confirm any specification changes. Date of print March 2013.

**Notes: (#1)** Towing capacity subject to country specific regulations. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle

and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0L 4x4 Diesel is towing 2,100kg its maximum Vehicle mass is 2,850kg in order to be within GCM of 4,950kg)

Available	•	Not Available	-
-----------	---	---------------	---